

119

Electric Oil Drum Pumps

EDR-OL

Workshop use Electric Oil Transfer pump

Compact & lightweight construction

ON/OFF Switch with LED Indicator

Built-in fuse for overload protection

Silenced motor makes almost no noise

Duty Cycle
15 minutes On / 30 Minutes Off

Self priming design
Allows for high suction lift even at dry start-up

Stainless steel filter built into the suction tube inlet prevents contaminants from entering & hence avoiding resultant damage

Discharge spout with
a. Aluminium die cast non-drip attachment
b. Welded steel holder that prevents entry of contaminants

Built-in 2" bung adaptor fits 205 litre (55 gal.) drums. Bung adapter can be adjusted by 0.6" (15 mm) to adjust to drums with varying heights.

Includes an additional bung thread converter for converting 2" standard bung threads to 2.5" x 5 mm buttress for using the same pumps with IBC's/Totes

Telescopic suction tube extends from 33-1/2" (850 mm) to 49" (1245 mm)

Suitable for use with
205 litres (55 gal.) drums or
1000 - 1250 litres (275-330 gal.)
IBC's/Totes

Also available in metered version:
High pressure positive displacement meter suitable for in-line applications

Digital Oval Gear Meter measures in Litres, US Gallons, Quarts, Pints

WETTED COMPONENTS
Viton, POM, Stainless Steel, PE, NBR, PP, Steel, Aluminium

RECOMMENDED USE
Motor oil, Hydraulic oil, Lubricants

DO NOT USE WITH
Gasoline, Corrosive chemicals, Lacquer thinners, any material that is not compatible with the pump construction

FEATURES

DELIVERS

UPTO
16 LPM
(4.2 GPM)

With SAE-30 Hydraulic oil



With 100V-240V, 50/60 Hz, AC Dual Voltage Power Adaptor

VARIANTS

ELECTRIC OIL PUMP	ELECTRIC OIL PUMP - METERED

SPECIFICATIONS

MOTOR TYPE	DC Brush Motor (5 Pole)
AC POWER ADAPTER	Input: 100 - 240 V AC, 50 / 60 Hz, Output: 20 V DC Constant Voltage, 6A max
MAX. VISCOSITY OF MEDIA	100 cSt / 465 SSU
TEMPERATURE	5° to 40°C (41° to 104°F)
ACCURACY*	±0.50%
REPEATABILITY*	0.25%
MAX RESETTABLE TOTAL	9,99,999 (six digits with × 100 indicator) units
MAX NON-RESETTABLE TOTAL	9,99,999 (six digits with × 100 indicator) units
LEAST COUNT/ RESOLUTION	Upto 0.001 Units

* Tested in laboratory conditions

ORDERING INFORMATION

CAT NR.	ORD NR.	DESCRIPTION	PLUG TYPE	BOX QTY.
ELECTRIC OIL PUMP				
EDR/OL/AC/AU	45840	With non-drip attachment & AC power adaptor with AU plug	Australian	4
EDR/OL/AC/EU	45841	With non-drip attachment & AC power adaptor with EU plug	European	4
EDR/OL/AC/UK	45842	With non-drip attachment & AC power adaptor with UK plug	UK	4
EDR/OL/AC/US	45843	With non-drip attachment & AC power adaptor with US plug	US	4
ELECTRIC OIL PUMP - METERED				
EDR/OLM/AC/AU	45844	With oil meter, non-drip attachment & AC power adaptor with AU plug	Australian	4
EDR/OLM/AC/EU	45845	With oil meter, non-drip attachment & AC power adaptor with EU plug	European	4
EDR/OLM/AC/UK	45846	With oil meter, non-drip attachment & AC power adaptor with UK plug	UK	4
EDR/OLM/AC/US	45847	With oil meter, non-drip attachment & AC power adaptor with US plug	US	4